

GHDE 10P HO ON/OFF PTS4  
8000005211



Switch-disconnectors OT 16...

Technical data



MAN. MTR. CNTLR.  
3E73



LR 58077

Short Circuit Ratings at 600 V AC		
kA	Fuse/A	Class of Fuse
10	30	CC, J, T or RK1
5	30	RK5

Suitable as  
Motor Disconnect

Technical data according to IEC 60947-3

		Size	A	16
		Switch type		OT16_
Rated insulation voltage and rated operational voltage AC20/DC20	Pollution degree 3		V	750
Dielectric strength		50 Hz 1 min.	kV	6
Rated impulse withstand voltage			kV	8
Rated thermal current and rated operational current AC20/DC20	ambient 40 °C	In open air	A	25
	ambient 40 °C	In enclosure	A	25
	ambient 60 °C	In enclosure	A	20
..with minimum conductor cross section		Cu	mm <sup>2</sup>	4
Rated operational current, AC-21A		up to 415 V	A	16
		440 – 690 V	A	16
Rated operational current, AC-22A		up to 415 V	A	16
		440 – 500 V	A	16
		690 V	A	16
Rated operational current, AC-23A		up to 415 V	A	16
		440 V	A	16
		500 V	A	16
		690 V	A	10
Rated operational current / poles in series, DC-21A		up to 48 V <sup>1)</sup>	A	16/1
		110 V	A	16/2
		220 V	A	16/3
		440 V	A	16/4
		500 V	A	16/4
		750 V	A	16/8
Rated operational current / poles in series, DC-22A		up to 48 V <sup>1)</sup>	A	16/1
		110 V	A	16/2
		220 V	A	16/3
		440 V	A	10/4
		750 V	A	16/8
Rated operational current / poles in series, DC-23A		up to 48 V <sup>1)</sup>	A	16/1
		110 V	A	16/2
		220 V	A	16/4
		440 V	A	10/4
		750 V	A	16/8
Rated operational power, AC-23A (These values are given for guidance and may vary acc. to the motor manufacturer)		220–240 V	kW	3
		400–415 V	kW	7.5
		440 V	kW	7.5
		500 V	kW	7.5
		690 V	kW	7.5
Rated breaking capacity, AC-23A		up to 415 V	A	128
		440 V	A	128
		500 V	A	128
		690 V	A	80
Rated breaking capacity/poles in series, DC-23A		up to 48 V	A	64/1
		110 V	A	64/2
		220 V	A	64/3
		440 V	A	40/4
		750 V	A	64/8
Rated conditional short-circuit current I <sub>p</sub> (r.m.s.) and corresponding max. allowed cut-off current I <sub>c</sub>	I <sub>p</sub> (r.m.s.)	50 kA	kA	6.5
	Max. OFA <sub>1</sub> fuse size gG/aM	≤ 415 V	A	40/32
	I <sub>p</sub> (r.m.s.)	100 kA	kA	
	Max. OFA <sub>1</sub> fuse size gG/aM	≤ 500 V	A	
The cut-off current I <sub>c</sub> refers to values listed by fuse manufacturers (single phase test acc. to IEC60269)	I <sub>p</sub> (r.m.s.)	10 kA	kA	
	Max. OFA <sub>1</sub> fuse size gG/aM	≤ 690 V	A	
	I <sub>p</sub> (r.m.s.)	50 kA	kA	4
	Max. OFA <sub>1</sub> fuse size gG/aM	≤ 690 V	A	25/16
Rated short-time withstand current	r.m.s. -value I <sub>ow</sub>	690V, 0.25 s	kA	
	r.m.s. -value I <sub>ow</sub>	690V, 1s	kA	0.5
Rated short circuit making capacity	Peak value I <sub>cm</sub>	690V/500V	kA	0.705
Rated capacitor power (The capacitor ratings are limited by the fuse link.)		400 – 415 V	kVAr	
Power loss / pole	At rated operational current		W	0.3
Mechanical endurance	Divide by two for operation cycles		Oper.	20000
Weight without accessories	3-pole		kg	0.11
	4-pole		kg	0.15
Cable size	Cu-wire size suitable for terminal clamps		mm <sup>2</sup>	0.75–10
			AWG	18–8
Terminal tightening torque	Counter torque required		Nm	0.8
Operating torque	3-pole switch-disconnector		Nm	1

<sup>1)</sup> Below 48 V, two poles in parallel up to OT 80 are recommended particularly in polluted atmosphere

<sup>2)</sup> 200A/min. 95 mm<sup>2</sup>, use busbar connections OEZXX6/13 or OZXT2